

# neomatik® HSG

HSG - Manual foam device

## Description

The **neomatik® HSG** is a device for cleaning floors, walls or appliances in commercial kitchens, as well as in the food processing industry. The detergent is applied as a foam onto the surfaces using the **neomatik® HSG** and, after being left to take effect, is rinsed off again with water.



Die Angaben dieses Merkblattes beruhen auf unseren derzeitigen Kenntnissen und Erfahrungen. Sie befreien den Verwender nicht von eigenen Prüfungen und Versuchen. Eine rechtlich verbindliche Zusicherung bestimmter Eigenschaften kann hieraus nicht abgeleitet werden.

With the above information, which is appropriate to our current knowledge we describe our product regarding possible safety necessities, but we do not involve any quality description or promise certain properties.

Chemische Fabrik Dr. Weigert GmbH & Co. KG  
Mühlenhagen 85, D - 20539 Hamburg  
Telefon: (040) 789 60 - 0  
Telefax: (040) 789 60 - 120  
E-Mail: [info@drweigert.de](mailto:info@drweigert.de)  
Internet: [www.drweigert.de](http://www.drweigert.de)

# neomatik<sup>®</sup> HSG

Art. Nr.: D070445

## Features

- Combination handle with:  
a coupling for an injector, jet pipe and hose  
ON/OFF function
- Foam injector with a coupling nipple for the combination handle
- 1.4 l chemical container
- Jet pipe
- Suction hose and filter
- Dosing nozzle kit, comprising:

Colour	Mixing ratio	in %
-	1:12	8.3%
Grey	1:12.4	8.1%
Black	1:12.8	7.8%
Beige	1:13.2	7.6%
Red	1:13.6	7.4%
White	1:14	7.1%
Blue	1:16	6.3%

Colour	Mixing ratio	in %
Light brown	1:18	5.5%
Green	1:26	3.8%
Orange	1:32	3.0%
Brown	1:38	2.6%
Yellow	1:42	2.3%
Violet	1:64	1.5%
Pink	1:128	0.8%

## Technical data

Water pressure: 2 to 8 bar  
Water temperature: max. 60 °C  
Mixing ratio: 0.8 to 8 %

## Safety instructions and maintenance:

- If it is to be operated permanently on the drinking water mains, the customer must integrate an approved reflux valve in accordance with DIN EN 1717.
- Our field service representatives, who are trained in the application, set the concentration correctly.
- Repairs may only be carried out by Dr. Weigert.
- Observe the operating manual.
- The product lines and the device must be cleaned after every use.